

Xilin OPS15

Ninghai, Zhejiang, China

onQ-30924

WAREHOUSE MOVERS & LIFTS - ORDER PICKERS NEW - SALE

Date Listed 28 Apr 2023 Reference OPS15

Power Type Battery Electric

Lift Capacity 3,307 lb(1,500 kg)

Mast Type Triplex (3 Stage)

Maximum Lift Height 354 in(9,000 mm)

Tyre Type Polyurethane / Vulkollan

Machine Height (Mast Lowered) 148 in(3,750 mm)

Machine Features Man up

Overhead Guard

ADDITIONAL INFORMATION

• Low gravity center provides good stability. • Advanced electric steering technology(EPS) is humanized designed, with automatic reset , height display and automatic deceleration at high lifting level.

• Finger tip control via joystick, Stepless speed control for driving, lifting and lowering speed is adjustable. • Buffer oil cylinder: the oil cylinder will automatic decelerate when off ground 500mm, to prevent impact and lower noises. • The mast and the frame are dividable and exchangeable. • Low battery protection setting prolongs the battery use time. • AC motor eliminates replacement of the carbon brush, provides good ramp starting performance and regenerative breaking functions. • Sideway battery is convenient for exchanging and maintaining. • The mast material is the special type imported from Germany. • The truck can automatic decelerate when quick turning. • High performance multi-function instrument has LED light and display function. LED indicators include battery indicator, fault indicator, Electric thermometer indicator, pedal indicator and hand break indicator. • Multi function display, include battery status, performance, working hour, accelerator, speed, the wheel position and traveling direction. • Press right and left keys to switch for different grades: high, normal, low, and lowest.





