

Xilin **FB35**

China

onQ-32579

FORKLIFTS - COUNTER BALANCE ELECTRIC NEW - SALE

Date Listed 28 Apr 2023

Reference FB35

Power Type Battery Electric Lift Capacity 7,716 lb(3,500 kg) **Mast Type** Triplex (3 Stage) **Maximum Lift Height** 276 in(7,000 mm) Tyre Type Solid / Puncture Proof

Machine Height (Mast Lowered)

Machine Features

81 in(2,045 mm)

Mast full free lift Overhead Guard

4 wheels

Front wheel drive

Charger Side shift

ADDITIONAL INFORMATION

High stability and safety • Cab design by SIP point, conform to EN-ISO 5353, ensures compartment with great comfort and fatigue-free operating. • Multifunction LCD digital display with digital service hour metre, battery discharge indicator, travel records, error code and warning displays. Provide fast and accurate monitoring truck status. • Mast cylinder lowering with buffering system: shock absorber steering axle with low noise. All of seal kits imported from Japan (NOK), transmission and working system have low noise. • With regenerative brake in reversing mode and regular brake pedal use, truck can be braked after foot leaving the pedal. reduce operator efforts and improve the brake life. • The optional of third safety pedal to reduce the driving speed while stacking and steering application. Ergonomics • Wide view mast, clear visibility. • Low height access step with wide steel non slip plate for easy entry and exit. • Cowlmounted hydraulic levers design offers big operation space. • Adjustable tilt steering column offers the most comfortable operator position. • Seat with safety belt and arm rest (The optional of Grammar or suspension type). • High-friction brake shoes are fee of asbestos. • With reverse mirror, front work light and back work light group. Easy maintenance • Floor board are easily removed for quick service assess. • Insulated battery cover gas-filled cylinders and easy to maintain. • The lifting motor under the floorboard for easy maintenance.