



**Xilin
CQDH15A**

China

onQ-30921

WAREHOUSE MOVERS & LIFTS - REACH TRUCKS & STACKERS
NEW - SALE

Date Listed	28 Apr 2023
Reference	CQDH15A
Power Type	Battery Electric
Lift Capacity	3,307 lb(1,500 kg)
Mast Type	Triplex (3 Stage)
Maximum Lift Height	220 in(5,600 mm)
Tyre Type	Polyurethane / Vulkollan
Machine Height (Mast Lowered)	99 in(2,505 mm)
Machine Features	Mast full free lift Pantograph/double reach

ADDITIONAL INFORMATION

STRUCTURAL ● Reach stacker with very compact design, have different option with platform or without platform. ● Low gravity, ensure safety operation. ● Water proof and dust proof motor structure, keeps the braking and motor more durable and reliable. ● Multi function display with BDI, hour meter and fault code. ● Vertical driving wheel ensures convenient maintenance and small turning radius. ● The mast and frame are dividable and exchangeable.

SAFETY AND EFFICIENCY ● Advanced AC drive motor eliminates replacement of carbon brush, with good ramp starting performance. ● Use Germany Frei handle to control driving speed, lifting/lowering speed, sideshift, fork reach and tilting. ● Cylinder have safety explosion proof valve, to avoid fork dropping suddenly when oil tube is broken. ensure the safety of operator. ● Automatic speed deceleration when lifting height is up 1.8M. ● Mast with micro switch limit the cylinder lifting height, avoid mast shock problems. ● Low voltage protection setting prolongs the battery life. (while battery less 20% only can drive no lifting) ● Option EPS power steering system, makes steering more light an reliable.

SERVICE ABILITY ● Platform and protection arm are disassembled, easy maintenance. ● The electronic components concentrated simplifies the circuit and makes easily assemble and access. ● Battery equipped with protect device, the trucks will automatic cut off power will when battery is under charging.