



**Xilin
CQDH18C**

China

onQ-30926

WAREHOUSE MOVERS & LIFTS - REACH TRUCKS & STACKERS
NEW - SALE

| | |
|--|--|
| Date Listed | 28 Apr 2023 |
| Reference | CQDH18C |
| Power Type | Battery Electric |
| Lift Capacity | 3,968 lb(1,800 kg) |
| Mast Type | Triplex (3 Stage) |
| Maximum Lift Height | 256 in(6,500 mm) |
| Tyre Type | Polyurethane / Vulkollan |
| Machine Height (Mast Lowered) | 112 in(2,840 mm) |
| Machine Features | Mast full free lift Pantograph/double reach Sit down Overhead Guard Side shift |

ADDITIONAL INFORMATION

SAFETY AND STABILITY ● AC motor drive with high efficiency, no need to replace carbon brush, very good ramp starting performance. ● Two model function can control the speed of lift and lowering. ● Low center of gravity, excellent stability for operation. ● Small turning radius, good turning performance. ● With advanced variable frequency AC motor free maintenance and excellent performance. ● Can control the speed of driving and lifting in the same time. ● Shock absorber system support good noise reduction. ● Wide view mast and clear visibility. ● With full free lifting, can work in the limited roof environment. ● Import proportional hydraulic valve, adjustable speed for lifting/lowering. ● Multi-function display: battery status, hour meter, fault code, slow running state, etc. ● Big power controller (350A) with big power electric motor (10KW), support excellent reliability. ● Double scissors reach fork let the reach distance up to 1000mm. ● The mast fixed with the frame, when fork move forward, the mast can become the balance weight, reduce the total service weight. ● With advanced 36V electric control system, smaller electric current, ensure the reliability of the battery system. ● High speed of lifting and lowering, 300% faster than normal type truck.

STRUCTURAL ● Side way battery is very convenient to do maintenance and replace batteries. ● CANbus technology reduces wiring complexity, making the line clear and orderly. increases the truck's reliability and easy to repair. ● The Mast can be separate from the frame, very good interchange ability (option).